



TeleControl Serie 21 , 2 Botones , 1 Velocidad, Alcance 100Mts 110~380V


Características Esenciales

- 3 Años de Garantía, Servicio y Atención al Cliente en Mexico

Especificaciones Técnicas

Codigo FCC	OFNF21	Fuente de Alimentación del Transmisor	2 AA batteries
Material	Glass-Fiber PA	Distancia de Control	Approx 60m (100 meters is customized)
Código de Seguridad	32 bits (4.3 billion)	Potencia del Transmisor	≤10dBm
Rango de Frecuencia	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz	Protección IEC Motor	IP65
Rango de temperatura de Trabajo	-40 ~ 185 °F / -40 ~ 85°C	Garantía	3 Year

F21-2S/2D TRANSMITTER
Small, economical, convenient



MODEL: F21-2S-TX
ITEM CODE: 921-002-001
Dimensions: 132 x 45 x 28 mm
Weight: 98g (without batteries)

Product Features:

- Two single/double speed buttons, one "STOP"
- 6 control contactors.
- With battery voltage warning device, the power supply is cut off during low power
- Safety key switch to prevent from unauthorized user.
- Program the button function by computer interface.
- Up/Down can be programmed to interlock or non-interlock.
- The spare button can be programmed to start, toggle or normal, etc.

Standard Configuration:

- One transmitter (with hanging belt)
- One dust bag
- One receiver
- Receiver with 1.6 meter cable
- Battery: One pair
- One receiver antenna.
- Operation and maintenance manual.

Safety features:

Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certifies.



Peso & Dimensiones

Peso Total 2 lbs / 1 Kg

Detalles del Empaque

Paquete 1 Peso Neto 2 lbs / 1 Kg

Paquete 1 Peso Bruto 2 lbs / 1 Kg

Paquete 1 Profundidad 9 in / 23 cm

Paquete 1 Ancho 7 in / 18 cm

Paquete 1 Altura 3 in / 8 cm

Referential Images / Imágenes Referenciales
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso