



## TeleControl Serie 21 , 4 Botones , 2 Velocidades, Alcance 100Mts

### Características Esenciales

- 3 Años de Garantía, Servicio y Atención al Cliente en Mexico

## Especificaciones Técnicas

<b>Codigo FCC</b>	OFNF21	<b>Fuente de Alimentación del Transmisor</b>	2 AA batteries
<b>Material</b>	Glass-Fiber PA	<b>Distancia de Control</b>	Approx 100m (200 meters is customized)
<b>Código de Seguridad</b>	32 bits (4.3 billion)	<b>Potencia del Transmisor</b>	≤10dBm
<b>Rango de Frecuencia</b>	VHF: 310~331 MHz; UHF: 425 ~ 446 MHz	<b>Protección IEC Motor</b>	IP65
<b>Rango de temperatura de Trabajo</b>	-40 ~ 185 °F / -40 ~ 85°C	<b>Garantía</b>	3 Year

## F21-4S/4D TRANSMITTER

Economical, safe, convenient



**MODEL:** F21-4S-TX  
**ITEM CODE:** 921-004-001  
**Dimensions:** 156 x 61 x 51 mm  
**Weight:** 255g (without batteries)

- Product Features:**
- 4 buttons (D means double steps), spare button
  - 8 control contactors.
  - With battery voltage warning device, the power supply is cut off during low power.
  - Program the button function by computer interface.
  - Up/Down, East/West can be programmed to interlock or non-interlock.
  - The spare button can be programmed to start, toggle or normal, etc.

- Standard Configuration:**
- One transmitter (with hanging belt)
  - One dust bag
  - One receiver
  - Receiver with 1.6 meter cable
  - Battery: One pair
  - One receiver antenna.
  - Operation and maintenance manual.


Transmitter Parameters: F21-TX	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Transmitter power	< 10dBm
Transmitter power supply	2 AA batteries
Safety code	32 bits (4.3 billion)
Temperature range	-40° C → 85° C
Control distance	Approx 100m (200 meters is customized)

- Safety features:**
- Each radio remote control system functions in all manner of operational conditions equipped with their own unique identity code (ID-Code). This means that only the correct control unit can activate and control its matching receiver (crane/machine) for maximum safety. The system is FCC and CE certificates.



**Start protection circuit**  
 Each system has a dedicated testing circuit. Before the system starts, the transmitting system tests all switch contacts and receiving system tests relays. Only if both procedures are passed the whole system starts working.

**MODEL:** F21-RXC  
**ITEM CODE:** 921-100-112  
**Dimensions:** 205 x 86 x 80 mm  
**Weight:** 620 g



Transmitter Parameters: F21-XRC	
Material	Glass-Fiber PA
Enclosure protection class	IP65
Frequency range	VHF: 310~331MHz; UHF: 425~446MHz
Receiver sensitivity	-110dBm
Receiver power supply	18~65V AC/DC, 65~440V AC/DC (optional)
Output contactor capacity	8A sealed relay output (with AC 250V/10A relays, 10A fuse)
Control distance	Approx 100m (200 meters is customized)
Safety code	32 bits (4.3 billion)
Temperature range	-40° C → 85° C



## Peso & Dimensiones

**Peso Total** 4 lbs / 2 Kg

## Detalles del Empaque

**Paquete 1 Peso Neto** 4 lbs / 2 Kg

**Paquete 1 Peso Bruto** 4 lbs / 2 Kg

**Paquete 1 Profundidad** 12 in / 31 cm

**Paquete 1 Ancho** 8 in / 21 cm

**Paquete 1 Altura** 2 in / 6 cm

Referential Images / Imágenes Referenciales  
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso