



## 3 ton Electric Chain Hoist w/ Power Trolley 1 Speed 208~240V 3½ 60HZ 16ft G100 Nickel Duty H4/M5

### Características Esenciales

- 3 Años de Garantía, Servicio y Atención al Cliente en Mexico

## Especificaciones Técnicas

|                                       |                                                                                                                                                                                                                     |                                                 |                  |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|------------------|
| <b>Capacidad de Carga</b>             | 3 ton                                                                                                                                                                                                               | <b>Altura de Izaje Estandard (Customizable)</b> | 16 ft / 5 m      |
| <b>Velocidad /min</b>                 | 21,26 ft @60Hz<br>5,4 mt @50Hz                                                                                                                                                                                      | <b>Numero de Velocidades</b>                    | 1 Speed          |
| <b>Voltaje</b>                        | 3 Phase 208~240V 50/60Hz                                                                                                                                                                                            | <b>Clase de Servicio</b>                        | H4/M5/2m/Class D |
| <b>Freno Motor</b>                    | Yes                                                                                                                                                                                                                 | <b>Protección IEC Motor</b>                     | IP55             |
| <b>Control</b>                        | Pendant Control IP66                                                                                                                                                                                                | <b>Voltaje del Control</b>                      | 24V              |
| <b>Tipo Transmisión / Reductor</b>    | Spur gearbox                                                                                                                                                                                                        | <b>Tipo de Cadena</b>                           | G100 Nickel      |
| <b>Dimensiones de la Cadena</b>       | 11.2 mm                                                                                                                                                                                                             | <b>Caidas de Cadena</b>                         | 1                |
| <b>Longitud de cadena</b>             | 16                                                                                                                                                                                                                  | <b>Humedad</b>                                  | 20%~90%          |
| <b>Temperatura</b>                    | -4 ~ 104° F / -20 ~ 40° C                                                                                                                                                                                           | <b>Potencia del Trolley</b>                     | 500              |
| <b>Velocidad del Trolley /min</b>     | 43,296 ft @60Hz<br>11 mt @50Hz                                                                                                                                                                                      | <b>Cantidad de Velocidades</b>                  | 1                |
| <b>Normas</b>                         | ASME HST-1 , ASME B30.16 , B30.17 , EN60204-35, EN ISO 12100:2010, EN 14492-2:2019, EN 60204-1:2018+A1:2025, EN IEC 61000-6-2:2019, EN IEC 61000-6-4:2019, EN IEC 61000-3-2:2019+A2:2024, EN 61000-3-3:2013+A2:2021 | <b>Garantía</b>                                 | 3 Year           |
| <b>Hoist Contactors Amps</b>          | 25A                                                                                                                                                                                                                 | <b>Hoist Contactor Brand</b>                    | sokar            |
| <b>Hoist Contactor Model</b>          | CJX2-2511                                                                                                                                                                                                           | <b>Hoist Contactor Coil Voltage</b>             | 24 V             |
| <b>IEC Hoist IP Protection</b>        | IP55                                                                                                                                                                                                                | <b>Pendant Control Yes No</b>                   | Yes              |
| <b>IEC Pendant Control Protection</b> | IP66                                                                                                                                                                                                                | <b>Pendant Control Emergency Stop</b>           | Yes              |

|                                                |              |                                        |            |
|------------------------------------------------|--------------|----------------------------------------|------------|
| <b>Trolley Motor Brake Type and DC Voltage</b> | DC170V       | <b>Trolley Motor Insulation Grade</b>  | F          |
| <b>Trolley Contactors Amps</b>                 | 12A          | <b>Trolley Contactors Brand</b>        | sokar      |
| <b>Trolley Contactors Model</b>                | CJX2-1211    | <b>Trolley Contactors Coil Voltage</b> | 24 V       |
| <b>Trolley Limit Switches</b>                  | Yes          | <b>Trolley Wheel Diameter</b>          | 124        |
| <b>Trolley Wheel Material</b>                  | No. 45 steel | <b>Trolley Minimum Turn Radius</b>     | 1,6        |
| <b>Trolley Beam Range</b>                      | 3.9" to 7"   | <b>Trolley Beam Extension Kit</b>      | up to 12"  |
| <b>Load Chain weight per foot [lbs]</b>        | 1.82         | <b>1st Package Type</b>                | Wood Crate |

## Peso & Dimensiones

**Peso Total** 385 lbs / 175 Kg

## Detalles del Empaque

**H Altura Muerta** 25.39

**A Altura Total** 22.05

**D Depth** 27.36

**W Ancho** 16.54

**J Boca Gancho** 2.32

**Peso Total (sin cable o cadena)** 293.79

Referential Images / Imágenes Referenciales  
Specifications may change without notice / las especificaciones pueden cambiar sin previo aviso